

ACCESSORIES

VZ series AIR RESERVOIR

VZ


Model	Port Size Rc (PT)	Bore Size Ø mm	Bore Stroke mm	Volume L	Pressure Range Kgf/cm ² (Kpa)
VZ -03L	1/4"	114	250	2.5	0 ~ 7 (0 ~ 700)
VZ -05L	3/8"	165	270	5	
VZ -10L	3/8"	200	375	10	
VZ -15L	3/8"	200	490	15	
VZ -20L	3/8"	244	490	20	
VZ -25L	3/8"	244	575	25	
VZ -30L	3/8"	244	660	30	
VZ -35L	3/8"	244	760	35	
VZ -40L	1/2"	300	590	40	
VZ -45L	1/2"	300	660	45	
VZ -50L	1/2"	300	760	50	
VZ -55L	1/2"	300	840	55	
VZ -60L	1/2"	300	870	60	

PU series PU TUBING

PU


Model	OD × ID (mm)	Standard Length (m)	Min. Bending Radius (mm)	Range of service temp. °C	Pressure Range Kgf/cm ² (Kpa)
PU0320	3 x 2	200	8	0 ~ 50	0 ~ 10 (0 ~ 1000)
PU0425	4 x 2.5	200	10		
PU0640	6 x 4	200	16		
PU0850	8 x 5	100	22		
PU1065	10 x 6.5	100	28		
PU1280	12 x 8	100	37		

※ Standard Color : Black 、 Blue 、 Transparent 、 (Also available in other color).

PN series NYLON TUBING

PN


Model	OD × ID (mm)	Standard Length (m)	Min. Bending Radius (mm)	Range of service temp. °C	Pressure Range Kgf/cm ²
PN0425	4 x 2.5	200	17	0 ~ 50	< 20
PN0640	6 x 4	100	37		
PN0850	8 x 5	100	48		
PN1075	10 x 7.5	100	66		
PN1290	12 x 9	100	76		

※ Standard Color : Transparent.